



**SAFETY DATA SHEET**  
**ULTRA FLEXJOINT WALL & FLOOR GROUT ANTHRACITE**

**1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING**

<b>PRODUCT NAME</b>	ULTRA FLEXJOINT WALL & FLOOR GROUT ANTHRACITE
<b>SUPPLIER</b>	Instarmac Group plc Danny Morson Way Birch Coppice Business Park Dordon, Tamworth Staffordshire. B78 1SE United Kingdom Tel: +44 (0) 1827 872244 Fax: +44 (0) 1827 874466 email@instarmac.co.uk www.instarmac.co.uk
<b>EMERGENCY TELEPHONE</b>	+44 (0)7971 217 347

**2 HAZARDS IDENTIFICATION**

Risk of serious damage to eyes. Irritating to respiratory system and skin. May cause sensitisation by skin contact.

**CLASSIFICATION** Xi;R37/38, R41. R43.

**3 COMPOSITION/INFORMATION ON INGREDIENTS**

Name	EC No.	CAS-No.	Content	Classification
BLACK PIGMENT		1133-86-4	1-10%	-
CALCIUM CARBONATE POWDERS			10-30%	-
PORTLAND CEMENT		65997-15-1	10-30%	Xi;R37/38,R41. R43.
SILICA SAND	238-878-4	14808-60-7	30-60%	-

The Full Text for all R-Phrases are Displayed in Section 16

**4 FIRST-AID MEASURES**

**GENERAL INFORMATION**

Risk of serious damage to eyes.

**INHALATION**

Move into fresh air and keep at rest. Get medical attention if any discomfort continues.

**INGESTION**

Do not induce vomiting. Immediately rinse mouth and drink plenty of water. Keep person under observation. If person becomes uncomfortable take to hospital along with these instructions.

**SKIN CONTACT**

Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if irritation persists after washing.

**EYE CONTACT**

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart. Continue to rinse for at least 15 minutes and get medical attention.

**5 FIRE-FIGHTING MEASURES**

**EXTINGUISHING MEDIA**

Water. Foam.

REVISION DATE: 08/06/2010

**ULTRA FLEXJOINT WALL & FLOOR GROUT ANTHRACITE****SPECIAL FIRE FIGHTING PROCEDURES**

No specific fire fighting procedure given.

**UNUSUAL FIRE & EXPLOSION HAZARDS**

No unusual fire or explosion hazards noted.

**6 ACCIDENTAL RELEASE MEASURES****PERSONAL PRECAUTIONS**

Wear protective clothing as described in Section 8 of this safety data sheet.

**ENVIRONMENTAL PRECAUTIONS**

Do not allow to enter drains, sewers or watercourses.

**SPILL CLEAN UP METHODS**

Remove spillage with vacuum cleaner. If not possible, collect spillage with shovel, broom or the like. Avoid generation and spreading of dust.

**7 HANDLING AND STORAGE****USAGE PRECAUTIONS**

Avoid spilling, skin and eye contact.

**STORAGE PRECAUTIONS**

Store in closed original container at temperatures between 5°C and 30°C. This product must be stored in unopened bags, clear of the ground in cool dry conditions and protected from excessive drafts. If stored correctly and used within 6 months of the date shown on the bag, the activity of the reducing agent will be maintained and this product will contain, when mixed with water, no more than 0.0002% (2 ppm) soluble Chromium (VI) of the total dry weight of the cement.

Shelf life in correct for sealed bags is 6 months. Please note: the use of this product after the end of the declared storage period may increase the risk of an allergic reaction.

**8 EXPOSURE CONTROLS/PERSONAL PROTECTION**

Name	Std	TWA - 8 hrs		STEL - 15 min		Notes
BLACK PIGMENT	WEL		3.5 mg/m <sup>3</sup>			
CALCIUM CARBONATE POWDERS			10 mg/m <sup>3</sup>			
PORTLAND CEMENT	WEL		10 mg/m <sup>3</sup>			
SILICA SAND	WEL		0.3 mg/m <sup>3</sup>			

WEL = Workplace Exposure Limit.

**PROTECTIVE EQUIPMENT****PROCESS CONDITIONS**

Provide eyewash station.

**ENGINEERING MEASURES**

Provide sufficient ventilation for operations causing dust formation.

**RESPIRATORY EQUIPMENT**

If ventilation is insufficient, suitable respiratory protection must be provided. Dust mask/respirator.

**HAND PROTECTION**

Use suitable protective gloves if risk of skin contact.

**EYE PROTECTION**

Wear dust resistant safety goggles where there is danger of eye contact.

REVISION DATE: 08/06/2010

**ULTRA FLEXJOINT WALL & FLOOR GROUT ANTHRACITE****OTHER PROTECTION**

Wear appropriate clothing to prevent any possibility of skin contact.

**HYGIENE MEASURES**

Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes contaminated. When using do not eat, drink or smoke. Wash contaminated clothing before reuse.

**9 PHYSICAL AND CHEMICAL PROPERTIES**

<b>APPEARANCE</b>	Powder, dust
<b>RELATIVE DENSITY</b>	1.6-2.0 @ 20°C

**10 STABILITY AND REACTIVITY****STABILITY**

Stable under normal temperature conditions and recommended use.

**MATERIALS TO AVOID**

Strong acids. Strong alkalis.

**11 TOXICOLOGICAL INFORMATION****INHALATION**

May cause damage to mucous membranes in nose, throat, lungs and bronchial system.

**INGESTION**

May cause discomfort if swallowed.

**SKIN CONTACT**

Prolonged contact with wet cement/mixture may cause burns.

**EYE CONTACT**

Risk of serious damage to eyes.

**12 ECOLOGICAL INFORMATION****ECOTOXICITY**

The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

**13 DISPOSAL CONSIDERATIONS****GENERAL INFORMATION**

Dispose of waste and residues in accordance with local authority requirements.

**14 TRANSPORT INFORMATION**

<b>GENERAL</b>	The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).
----------------	---

**15 REGULATORY INFORMATION****LABELLING**

Irritant

**CONTAINS** PORTLAND CEMENT

**RISK PHRASES**

R37/38	Irritating to respiratory system and skin.
R41	Risk of serious damage to eyes.

REVISION DATE: 08/06/2010

**ULTRA FLEXJOINT WALL & FLOOR GROUT ANTHRACITE**

R43 May cause sensitisation by skin contact.

**SAFETY PHRASES**

S24/25 Avoid contact with skin and eyes.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S37/39 Wear suitable gloves and eye/face protection.

S46 If swallowed, seek medical advice immediately and show this container or label.

S51 Use only in well-ventilated areas.

S64 If swallowed, rinse mouth with water (only if the person is conscious).

**UK REGULATORY REFERENCES**

Chemicals (Hazard Information &amp; Packaging) Regulations.

**ENVIRONMENTAL LISTING**

Control of Pollution Act 1974.

**EU DIRECTIVES**

Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC. Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

**APPROVED CODE OF PRACTICE**

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply.

**GUIDANCE NOTES**

Workplace Exposure Limits EH40.

**NATIONAL REGULATIONS**

Workplace Exposure Limits 2005 (EH40) The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2007 (CDG 2007)

**16 OTHER INFORMATION****GENERAL INFORMATION**

If further information on training is required contact Instarmac Group plc

**REVISION DATE** 08/06/2010**REV. NO./REPL. SDS GENERATED** 3**RISK PHRASES IN FULL**

NC Not classified.

R37/38 Irritating to respiratory system and skin.

R41 Risk of serious damage to eyes.

R43 May cause sensitisation by skin contact.

**DISCLAIMER**

The purpose of the above information is to describe the products only in terms of health and safety requirements. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. It is the users obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date specified.

All goods are supplied in accordance with Instarmac Group plc's general conditions of sale, copies of which may be obtained by telephoning sales on 01827 872244



**SAFETY DATA SHEET**  
**ULTRA FLEXJOINT WALL & FLOOR GROUT CHOCOLATE**

**1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING**

<b>PRODUCT NAME</b>	ULTRA FLEXJOINT WALL & FLOOR GROUT CHOCOLATE
<b>SUPPLIER</b>	Instarmac Group plc Danny Morson Way Birch Coppice Business Park Dordon, Tamworth Staffordshire. B78 1SE United Kingdom Tel: +44 (0) 1827 872244 Fax: +44 (0) 1827 874466 email@instarmac.co.uk www.instarmac.co.uk
<b>EMERGENCY TELEPHONE</b>	+44 (0)7971 217 347

**2 HAZARDS IDENTIFICATION**

Risk of serious damage to eyes. Irritating to respiratory system and skin. May cause sensitisation by skin contact.

**CLASSIFICATION** Xi;R37/38, R41. R43.

**3 COMPOSITION/INFORMATION ON INGREDIENTS**

Name	EC No.	CAS-No.	Content	Classification
PORTLAND CEMENT		65997-15-1	10-30%	Xi;R37/38,R41. R43.
SILICA SAND	238-878-4	14808-60-7	30-60%	-
VINYL ACETATE COPOLYMER			1-10%	-

The Full Text for all R-Phrases are Displayed in Section 16

**4 FIRST-AID MEASURES**

**GENERAL INFORMATION**

Risk of serious damage to eyes.

**INHALATION**

Move into fresh air and keep at rest. Get medical attention if any discomfort continues.

**INGESTION**

Do not induce vomiting. Immediately rinse mouth and drink plenty of water. Keep person under observation. If person becomes uncomfortable take to hospital along with these instructions.

**SKIN CONTACT**

Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if irritation persists after washing.

**EYE CONTACT**

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart. Continue to rinse for at least 15 minutes and get medical attention.

**5 FIRE-FIGHTING MEASURES**

**EXTINGUISHING MEDIA**

Water. Foam.

**SPECIAL FIRE FIGHTING PROCEDURES**

No specific fire fighting procedure given.

**UNUSUAL FIRE & EXPLOSION HAZARDS**

No unusual fire or explosion hazards noted.

**ULTRA FLEXJOINT WALL & FLOOR GROUT CHOCOLATE****6 ACCIDENTAL RELEASE MEASURES****PERSONAL PRECAUTIONS**

Wear protective clothing as described in Section 8 of this safety data sheet.

**ENVIRONMENTAL PRECAUTIONS**

Do not allow to enter drains, sewers or watercourses.

**SPILL CLEAN UP METHODS**

Remove spillage with vacuum cleaner. If not possible, collect spillage with shovel, broom or the like. Avoid generation and spreading of dust.

**7 HANDLING AND STORAGE****USAGE PRECAUTIONS**

Avoid spilling, skin and eye contact.

**STORAGE PRECAUTIONS**

Store in closed original container at temperatures between 5°C and 30°C. This product must be stored in unopened bags, clear of the ground in cool dry conditions and protected from excessive drafts. If stored correctly and used within 6 months of the date shown on the bag, the activity of the reducing agent will be maintained and this product will contain, when mixed with water, no more than 0.0002% (2 ppm) soluble Chromium (VI) of the total dry weight of the cement.

Shelf life in correct for sealed bags is 6 months. Please note: the use of this product after the end of the declared storage period may increase the risk of an allergic reaction.

**8 EXPOSURE CONTROLS/PERSONAL PROTECTION**

Name	Std	TWA - 8 hrs		STEL - 15 min		Notes
PORTLAND CEMENT	WEL		10 mg/m <sup>3</sup>			
SILICA SAND	WEL		0.3 mg/m <sup>3</sup>			
VINYL ACETATE COPOLYMER	WEL		4 mg/m <sup>3</sup>			

WEL = Workplace Exposure Limit.

**PROTECTIVE EQUIPMENT****PROCESS CONDITIONS**

Provide eyewash station.

**ENGINEERING MEASURES**

Provide sufficient ventilation for operations causing dust formation.

**RESPIRATORY EQUIPMENT**

If ventilation is insufficient, suitable respiratory protection must be provided. Dust mask/respirator.

**HAND PROTECTION**

Use suitable protective gloves if risk of skin contact.

**EYE PROTECTION**

Wear dust resistant safety goggles where there is danger of eye contact.

**OTHER PROTECTION**

Wear appropriate clothing to prevent any possibility of skin contact.

**HYGIENE MEASURES**

Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes contaminated. When using do not eat, drink or smoke. Wash contaminated clothing before reuse.

**9 PHYSICAL AND CHEMICAL PROPERTIES**

**APPEARANCE** Powder, dust

**RELATIVE DENSITY** 1.6-2.0 @ 20°C

**10 STABILITY AND REACTIVITY**

REVISION DATE: 05/08/2009

**ULTRA FLEXJOINT WALL & FLOOR GROUT CHOCOLATE****STABILITY**

Stable under normal temperature conditions and recommended use.

**MATERIALS TO AVOID**

Strong acids. Strong alkalis.

**11 TOXICOLOGICAL INFORMATION****INHALATION**

May cause damage to mucous membranes in nose, throat, lungs and bronchial system.

**INGESTION**

May cause discomfort if swallowed.

**SKIN CONTACT**

Prolonged contact with wet cement/mixture may cause burns.

**EYE CONTACT**

Risk of serious damage to eyes.

**12 ECOLOGICAL INFORMATION****ECOTOXICITY**

The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

**13 DISPOSAL CONSIDERATIONS****GENERAL INFORMATION**

Dispose of waste and residues in accordance with local authority requirements.

**14 TRANSPORT INFORMATION****GENERAL**

The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

**15 REGULATORY INFORMATION****LABELLING**

Irritant

**CONTAINS**

PORTLAND CEMENT

**RISK PHRASES**

R41	Risk of serious damage to eyes.
R43	May cause sensitisation by skin contact.
R37/38	Irritating to respiratory system and skin.

**SAFETY PHRASES**

S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S46	If swallowed, seek medical advice immediately and show this container or label.
S51	Use only in well-ventilated areas.
S24/25	Avoid contact with skin and eyes.
S37/39	Wear suitable gloves and eye/face protection.
S64	If swallowed, rinse mouth with water (only if the person is conscious).

**UK REGULATORY REFERENCES**

Chemicals (Hazard Information &amp; Packaging) Regulations.

**ENVIRONMENTAL LISTING**

Control of Pollution Act 1974.

REVISION DATE: 05/08/2009

**ULTRA FLEXJOINT WALL & FLOOR GROUT CHOCOLATE****EU DIRECTIVES**

Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC. Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

**APPROVED CODE OF PRACTICE**

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply.

**GUIDANCE NOTES**

Workplace Exposure Limits EH40.

**NATIONAL REGULATIONS**

Workplace Exposure Limits 2005 (EH40) The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2007 (CDG 2007)

**16 OTHER INFORMATION****GENERAL INFORMATION**

If further information on training is required contact Instarmac Group plc

**REVISION DATE** 05/08/2009

**REV. NO./REPL. SDS GENERATED** 3

**RISK PHRASES IN FULL**

NC	Not classified.
R37/38	Irritating to respiratory system and skin.
R41	Risk of serious damage to eyes.
R43	May cause sensitisation by skin contact.

**DISCLAIMER**

The purpose of the above information is to describe the products only in terms of health and safety requirements. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. It is the users obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date specified.

All goods are supplied in accordance with Instarmac Group plc's general conditions of sale, copies of which may be obtained by telephoning sales on 01827 872244



**SAFETY DATA SHEET**  
**ULTRA FLEXJOINT WALL & FLOOR GROUT GREY**

**1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING**

**PRODUCT NAME** ULTRA FLEXJOINT WALL & FLOOR GROUT GREY  
**SUPPLIER** Instarmac Group plc  
Danny Morson Way  
Birch Coppice Business Park  
Dordon, Tamworth  
Staffordshire. B78 1SE  
United Kingdom  
Tel: +44 (0) 1827 872244  
Fax: +44 (0) 1827 874466  
email@instarmac.co.uk  
www.instarmac.co.uk  
**EMERGENCY TELEPHONE** +44 (0)7971 217 347

**2 HAZARDS IDENTIFICATION**

Risk of serious damage to eyes. Irritating to respiratory system and skin. May cause sensitisation by skin contact.

**CLASSIFICATION** Xi;R37/38, R41. R43.

**3 COMPOSITION/INFORMATION ON INGREDIENTS**

Name	EC No.	CAS-No.	Content	Classification
PORTLAND CEMENT		65997-15-1	10-30%	Xi;R37/38,R41. R43.
SILICA SAND	238-878-4	14808-60-7	30-60%	-
VINYL ACETATE COPOLYMER			1-10%	-

The Full Text for all R-Phrases are Displayed in Section 16

**4 FIRST-AID MEASURES**

**GENERAL INFORMATION**

Risk of serious damage to eyes.

**INHALATION**

Move into fresh air and keep at rest. Get medical attention if any discomfort continues.

**INGESTION**

Do not induce vomiting. Immediately rinse mouth and drink plenty of water. Keep person under observation. If person becomes uncomfortable take to hospital along with these instructions.

**SKIN CONTACT**

Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if irritation persists after washing.

**EYE CONTACT**

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart. Continue to rinse for at least 15 minutes and get medical attention.

**5 FIRE-FIGHTING MEASURES**

**EXTINGUISHING MEDIA**

Water. Foam.

**SPECIAL FIRE FIGHTING PROCEDURES**

No specific fire fighting procedure given.

## ULTRA FLEXJOINT WALL & FLOOR GROUT GREY

### UNUSUAL FIRE & EXPLOSION HAZARDS

No unusual fire or explosion hazards noted.

## 6 ACCIDENTAL RELEASE MEASURES

### PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet.

### ENVIRONMENTAL PRECAUTIONS

Do not allow to enter drains, sewers or watercourses.

### SPILL CLEAN UP METHODS

Remove spillage with vacuum cleaner. If not possible, collect spillage with shovel, broom or the like. Avoid generation and spreading of dust.

## 7 HANDLING AND STORAGE

### USAGE PRECAUTIONS

Avoid spilling, skin and eye contact.

### STORAGE PRECAUTIONS

Store in closed original container at temperatures between 5°C and 30°C. This product must be stored in unopened bags, clear of the ground in cool dry conditions and protected from excessive drafts. If stored correctly and used within 6 months of the date shown on the bag, the activity of the reducing agent will be maintained and this product will contain, when mixed with water, no more than 0.0002% (2 ppm) soluble Chromium (VI) of the total dry weight of the cement.

Shelf life in correct for sealed bags is 6 months. Please note: the use of this product after the end of the declared storage period may increase the risk of an allergic reaction.

## 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	TWA - 8 hrs		STEL - 15 min		Notes
PORTLAND CEMENT	WEL		10 mg/m <sup>3</sup>			
SILICA SAND	WEL		0.3 mg/m <sup>3</sup>			
VINYL ACETATE COPOLYMER	WEL		4 mg/m <sup>3</sup>			

WEL = Workplace Exposure Limit.

### PROTECTIVE EQUIPMENT



### PROCESS CONDITIONS

Provide eyewash station.

### ENGINEERING MEASURES

Provide sufficient ventilation for operations causing dust formation.

### RESPIRATORY EQUIPMENT

If ventilation is insufficient, suitable respiratory protection must be provided. Dust mask/respirator.

### HAND PROTECTION

Use suitable protective gloves if risk of skin contact.

### EYE PROTECTION

Wear dust resistant safety goggles where there is danger of eye contact.

### OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of skin contact.

### HYGIENE MEASURES

Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes contaminated. When using do not eat, drink or smoke. Wash contaminated clothing before reuse.

## ULTRA FLEXJOINT WALL & FLOOR GROUT GREY

### 9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Powder, dust
RELATIVE DENSITY	1.6-2.0 @ 20°C

### 10 STABILITY AND REACTIVITY

#### STABILITY

Stable under normal temperature conditions and recommended use.

#### MATERIALS TO AVOID

Strong acids. Strong alkalis.

### 11 TOXICOLOGICAL INFORMATION

#### INHALATION

May cause damage to mucous membranes in nose, throat, lungs and bronchial system.

#### INGESTION

May cause discomfort if swallowed.

#### SKIN CONTACT

Prolonged contact with wet cement/mixture may cause burns.

#### EYE CONTACT

Risk of serious damage to eyes.

### 12 ECOLOGICAL INFORMATION

#### ECOTOXICITY

The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

### 13 DISPOSAL CONSIDERATIONS

#### GENERAL INFORMATION

Dispose of waste and residues in accordance with local authority requirements.

### 14 TRANSPORT INFORMATION

GENERAL	The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).
---------	---

### 15 REGULATORY INFORMATION

#### LABELLING



Irritant

CONTAINS	PORTLAND CEMENT
----------	-----------------

#### RISK PHRASES

R37/38	Irritating to respiratory system and skin.
R41	Risk of serious damage to eyes.
R43	May cause sensitisation by skin contact.

#### SAFETY PHRASES

S24/25	Avoid contact with skin and eyes.
S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

**ULTRA FLEXJOINT WALL & FLOOR GROUT GREY**

S37/39	Wear suitable gloves and eye/face protection.
S46	If swallowed, seek medical advice immediately and show this container or label.
S51	Use only in well-ventilated areas.
S64	If swallowed, rinse mouth with water (only if the person is conscious).

**UK REGULATORY REFERENCES**

Chemicals (Hazard Information & Packaging) Regulations.

**ENVIRONMENTAL LISTING**

Control of Pollution Act 1974.

**EU DIRECTIVES**

Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC. Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

**APPROVED CODE OF PRACTICE**

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply.

**GUIDANCE NOTES**

Workplace Exposure Limits EH40.

**NATIONAL REGULATIONS**

Workplace Exposure Limits 2005 (EH40) The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2007 (CDG 2007)

**16 OTHER INFORMATION****GENERAL INFORMATION**

If further information on training is required contact Instarmac Group plc

**REVISION DATE** 09/07/2009

**REV. NO./REPL. SDS GENERATED** 2

**RISK PHRASES IN FULL**

NC	Not classified.
R37/38	Irritating to respiratory system and skin.
R41	Risk of serious damage to eyes.
R43	May cause sensitisation by skin contact.

**DISCLAIMER**

The purpose of the above information is to describe the products only in terms of health and safety requirements. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. It is the users obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date specified.

All goods are supplied in accordance with Instarmac Group plc's general conditions of sale, copies of which may be obtained by telephoning sales on 01827 872244



**SAFETY DATA SHEET**  
**ULTRA FLEXJOINT WALL & FLOOR GROUT LIMESTONE**

**1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING**

<b>PRODUCT NAME</b>	ULTRA FLEXJOINT WALL & FLOOR GROUT LIMESTONE
<b>SUPPLIER</b>	Instarmac Group plc Danny Morson Way Birch Coppice Business Park Dordon, Tamworth Staffordshire. B78 1SE United Kingdom Tel: +44 (0) 1827 872244 Fax: +44 (0) 1827 874466 email@instarmac.co.uk www.instarmac.co.uk
<b>EMERGENCY TELEPHONE</b>	+44 (0)7971 217 347

**2 HAZARDS IDENTIFICATION**

Risk of serious damage to eyes. Irritating to respiratory system and skin.

**CLASSIFICATION** Xi;R37/38, R41.

**3 COMPOSITION/INFORMATION ON INGREDIENTS**

Name	EC No.	CAS-No.	Content	Classification
CALCIUM CARBONATE POWDERS			10-30%	-
SILICA SAND	238-878-4	14808-60-7	30-60%	-
WHITE OPC			10-30%	Xi;R41,R37/38.

The Full Text for all R-Phrases are Displayed in Section 16

**4 FIRST-AID MEASURES**

**GENERAL INFORMATION**

Risk of serious damage to eyes.

**INHALATION**

Move into fresh air and keep at rest. Get medical attention if any discomfort continues.

**INGESTION**

DO NOT INDUCE VOMITING! Immediately rinse mouth and drink plenty of water (200-300 ml).

**SKIN CONTACT**

Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if irritation persists after washing.

**EYE CONTACT**

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart. Continue to rinse for at least 15 minutes and get medical attention.

**5 FIRE-FIGHTING MEASURES**

**EXTINGUISHING MEDIA**

Water. Foam.

**SPECIAL FIRE FIGHTING PROCEDURES**

No specific fire fighting procedure given.

**UNUSUAL FIRE & EXPLOSION HAZARDS**

No unusual fire or explosion hazards noted.

**6 ACCIDENTAL RELEASE MEASURES**

REVISION DATE: 13/11/2009

**ULTRA FLEXJOINT WALL & FLOOR GROUT LIMESTONE****PERSONAL PRECAUTIONS**

Wear protective clothing as described in Section 8 of this safety data sheet.

**ENVIRONMENTAL PRECAUTIONS**

Do not allow to enter drains, sewers or watercourses.

**SPILL CLEAN UP METHODS**

Remove spillage with vacuum cleaner. If not possible, collect spillage with shovel, broom or the like. Avoid generation and spreading of dust.

**7 HANDLING AND STORAGE****USAGE PRECAUTIONS**

Avoid spilling, skin and eye contact.

**STORAGE PRECAUTIONS**

Avoid frost. Store in closed original container at temperatures between 5°C and 30°C.

**8 EXPOSURE CONTROLS/PERSONAL PROTECTION**

Name	Std	TWA - 8 hrs		STEL - 15 min		Notes
CALCIUM CARBONATE POWDERS			10 mg/m <sup>3</sup>			
SILICA SAND	WEL		0.3 mg/m <sup>3</sup>			
WHITE OPC	WEL		4 mg/m <sup>3</sup>			

WEL = Workplace Exposure Limit.

**PROTECTIVE EQUIPMENT****PROCESS CONDITIONS**

Provide eyewash station.

**ENGINEERING MEASURES**

Provide sufficient ventilation for operations causing dust formation.

**RESPIRATORY EQUIPMENT**

If ventilation is insufficient, suitable respiratory protection must be provided. Dust mask/respirator.

**HAND PROTECTION**

Use suitable protective gloves if risk of skin contact.

**EYE PROTECTION**

Wear dust resistant safety goggles where there is danger of eye contact.

**OTHER PROTECTION**

Wear appropriate clothing to prevent any possibility of skin contact.

**HYGIENE MEASURES**

Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes contaminated. When using do not eat, drink or smoke. Wash contaminated clothing before reuse.

**9 PHYSICAL AND CHEMICAL PROPERTIES**

APPEARANCE	Powder, dust
RELATIVE DENSITY	1.6-2.0 @ 20°C

**10 STABILITY AND REACTIVITY****STABILITY**

Stable under normal temperature conditions and recommended use.

**MATERIALS TO AVOID**

Strong acids. Strong alkalis.

**ULTRA FLEXJOINT WALL & FLOOR GROUT LIMESTONE****11 TOXICOLOGICAL INFORMATION****INHALATION**

May cause damage to mucous membranes in nose, throat, lungs and bronchial system.

**INGESTION**

May cause discomfort if swallowed.

**SKIN CONTACT**

Prolonged contact with wet cement/mixture may cause burns.

**EYE CONTACT**

Risk of serious damage to eyes.

**12 ECOLOGICAL INFORMATION****ECOTOXICITY**

The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

**13 DISPOSAL CONSIDERATIONS****GENERAL INFORMATION**

Dispose of waste and residues in accordance with local authority requirements.

**14 TRANSPORT INFORMATION****GENERAL**

The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

**15 REGULATORY INFORMATION****LABELLING**

Irritant

**RISK PHRASES**

R37/38 Irritating to respiratory system and skin.  
R41 Risk of serious damage to eyes.

**SAFETY PHRASES**

S24/25 Avoid contact with skin and eyes.  
S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
S37/39 Wear suitable gloves and eye/face protection.  
S46 If swallowed, seek medical advice immediately and show this container or label.  
S51 Use only in well-ventilated areas.  
S64 If swallowed, rinse mouth with water (only if the person is conscious).

**UK REGULATORY REFERENCES**

Chemicals (Hazard Information & Packaging) Regulations.

**ENVIRONMENTAL LISTING**

Control of Pollution Act 1974.

**EU DIRECTIVES**

Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC.

**APPROVED CODE OF PRACTICE**

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply.

**GUIDANCE NOTES**

Workplace Exposure Limits EH40.

REVISION DATE: 13/11/2009

**ULTRA FLEXJOINT WALL & FLOOR GROUT LIMESTONE****NATIONAL REGULATIONS**

Workplace Exposure Limits 2005 (EH40) The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2007 (CDG 2007)

**16 OTHER INFORMATION****GENERAL INFORMATION**

If further information on training is required contact Instarmac Group plc

**REVISION DATE** 13/11/2009

**REV. NO./REPL. SDS GENERATED** 3

**RISK PHRASES IN FULL**

NC	Not classified.
R37/38	Irritating to respiratory system and skin.
R41	Risk of serious damage to eyes.

**DISCLAIMER**

The purpose of the above information is to describe the products only in terms of health and safety requirements. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. It is the users obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date specified.

All goods are supplied in accordance with Instarmac Group plc's general conditions of sale, copies of which may be obtained by telephoning sales on 01827 872244



**SAFETY DATA SHEET**  
**ULTRA FLEXJOINT WALL & FLOOR GROUT SANDSTONE**

**1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING**

<b>PRODUCT NAME</b>	ULTRA FLEXJOINT WALL & FLOOR GROUT SANDSTONE
<b>SUPPLIER</b>	Instarmac Group plc Danny Morson Way Birch Coppice Business Park Dordon, Tamworth Staffordshire. B78 1SE United Kingdom Tel: +44 (0) 1827 872244 Fax: +44 (0) 1827 874466 email@instarmac.co.uk www.instarmac.co.uk
<b>EMERGENCY TELEPHONE</b>	+44 (0)7971 217 347

**2 HAZARDS IDENTIFICATION**

Risk of serious damage to eyes. Irritating to respiratory system and skin.

**CLASSIFICATION** Xi;R37/38, R41.

**3 COMPOSITION/INFORMATION ON INGREDIENTS**

Name	EC No.	CAS-No.	Content	Classification
CALCIUM CARBONATE POWDERS			10-30%	-
METHYL-2H or METHYL-4 (3:1) Mixture of EC NO 220-239-6		55965-84-9	< 1 %	T;R23/24/25 C;R34 R43 N;R50/53
SILICA SAND	238-878-4	14808-60-7	30-60%	-
VINYL ACETATE COPOLYMER			1-10%	-
WHITE OPC			10-30%	Xi;R41,R37/38.

The Full Text for all R-Phrases are Displayed in Section 16

**4 FIRST-AID MEASURES**

**GENERAL INFORMATION**

Risk of serious damage to eyes.

**INHALATION**

Move into fresh air and keep at rest. Get medical attention if any discomfort continues.

**INGESTION**

DO NOT INDUCE VOMITING! Immediately rinse mouth and drink plenty of water (200-300 ml).

**SKIN CONTACT**

Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if irritation persists after washing.

**EYE CONTACT**

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart. Continue to rinse for at least 15 minutes and get medical attention.

**5 FIRE-FIGHTING MEASURES**

**EXTINGUISHING MEDIA**

Water. Foam.

**SPECIAL FIRE FIGHTING PROCEDURES**

No specific fire fighting procedure given.

REVISION DATE: 13/11/2009

**ULTRA FLEXJOINT WALL & FLOOR GROUT SANDSTONE****UNUSUAL FIRE & EXPLOSION HAZARDS**

No unusual fire or explosion hazards noted.

**6 ACCIDENTAL RELEASE MEASURES****PERSONAL PRECAUTIONS**

Wear protective clothing as described in Section 8 of this safety data sheet.

**ENVIRONMENTAL PRECAUTIONS**

Do not allow to enter drains, sewers or watercourses.

**SPILL CLEAN UP METHODS**

Remove spillage with vacuum cleaner. If not possible, collect spillage with shovel, broom or the like. Avoid generation and spreading of dust.

**7 HANDLING AND STORAGE****USAGE PRECAUTIONS**

Avoid spilling, skin and eye contact.

**STORAGE PRECAUTIONS**

Avoid frost. Store in closed original container at temperatures between 5°C and 30°C.

**8 EXPOSURE CONTROLS/PERSONAL PROTECTION**

Name	Std	TWA - 8 hrs	STEL - 15 min	Notes
CALCIUM CARBONATE POWDERS		10 mg/m <sup>3</sup>		
METHYL-2H or METHYL-4 (3:1) Mixture of EC NO 220-239-6	WEL	0.20 mg/m <sup>3</sup>		
SILICA SAND	WEL	0.3 mg/m <sup>3</sup>		
VINYL ACETATE COPOLYMER	WEL	4 mg/m <sup>3</sup>		
WHITE OPC	WEL	4 mg/m <sup>3</sup>		

**WEL = Workplace Exposure Limit.****PROTECTIVE EQUIPMENT****PROCESS CONDITIONS**

Provide eyewash station.

**ENGINEERING MEASURES**

Provide sufficient ventilation for operations causing dust formation.

**RESPIRATORY EQUIPMENT**

If ventilation is insufficient, suitable respiratory protection must be provided. Dust mask/respirator.

**HAND PROTECTION**

Use suitable protective gloves if risk of skin contact.

**EYE PROTECTION**

Wear dust resistant safety goggles where there is danger of eye contact.

**OTHER PROTECTION**

Wear appropriate clothing to prevent any possibility of skin contact.

**HYGIENE MEASURES**

Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes contaminated. When using do not eat, drink or smoke. Wash contaminated clothing before reuse.

**9 PHYSICAL AND CHEMICAL PROPERTIES****APPEARANCE**

Powder, dust

**RELATIVE DENSITY**

1.6-2.0 @ 20°C

**ULTRA FLEXJOINT WALL & FLOOR GROUT SANDSTONE****10 STABILITY AND REACTIVITY****STABILITY**

Stable under normal temperature conditions and recommended use.

**MATERIALS TO AVOID**

Strong acids. Strong alkalis.

**11 TOXICOLOGICAL INFORMATION****INHALATION**

May cause damage to mucous membranes in nose, throat, lungs and bronchial system.

**INGESTION**

May cause discomfort if swallowed.

**SKIN CONTACT**

Prolonged contact with wet cement/mixture may cause burns.

**EYE CONTACT**

Risk of serious damage to eyes.

**12 ECOLOGICAL INFORMATION****ECOTOXICITY**

The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

**13 DISPOSAL CONSIDERATIONS****GENERAL INFORMATION**

Dispose of waste and residues in accordance with local authority requirements.

**14 TRANSPORT INFORMATION****GENERAL**

The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

**15 REGULATORY INFORMATION****LABELLING**

Irritant

**RISK PHRASES**

R37/38 Irritating to respiratory system and skin.  
R41 Risk of serious damage to eyes.

**SAFETY PHRASES**

S24/25 Avoid contact with skin and eyes.  
S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
S37/39 Wear suitable gloves and eye/face protection.  
S46 If swallowed, seek medical advice immediately and show this container or label.  
S51 Use only in well-ventilated areas.  
S64 If swallowed, rinse mouth with water (only if the person is conscious).

**UK REGULATORY REFERENCES**

Chemicals (Hazard Information & Packaging) Regulations.

**ENVIRONMENTAL LISTING**

Control of Pollution Act 1974.

REVISION DATE: 13/11/2009

**ULTRA FLEXJOINT WALL & FLOOR GROUT SANDSTONE****EU DIRECTIVES**

Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC.

**APPROVED CODE OF PRACTICE**

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply.

**GUIDANCE NOTES**

Workplace Exposure Limits EH40.

**NATIONAL REGULATIONS**

Workplace Exposure Limits 2005 (EH40) The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2007 (CDG 2007)

**16 OTHER INFORMATION****GENERAL INFORMATION**

If further information on training is required contact Instarmac Group plc

**REVISION DATE** 13/11/2009

**REV. NO./REPL. SDS GENERATED** 2

**RISK PHRASES IN FULL**

NC	Not classified.
R23/24/25	Toxic by inhalation, in contact with skin and if swallowed.
R34	Causes burns.
R37/38	Irritating to respiratory system and skin.
R41	Risk of serious damage to eyes.
R43	May cause sensitisation by skin contact.
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**DISCLAIMER**

The purpose of the above information is to describe the products only in terms of health and safety requirements. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. It is the users obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date specified.

All goods are supplied in accordance with Instarmac Group plc's general conditions of sale, copies of which may be obtained by telephoning sales on 01827 872244



**SAFETY DATA SHEET**  
**ULTRA FLEXJOINT WALL & FLOOR GROUT WHITE**

**1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING**

<b>PRODUCT NAME</b>	ULTRA FLEXJOINT WALL & FLOOR GROUT WHITE
<b>SUPPLIER</b>	Instarmac Group plc Danny Morson Way Birch Coppice Business Park Dordon, Tamworth Staffordshire. B78 1SE United Kingdom Tel: +44 (0) 1827 872244 Fax: +44 (0) 1827 874466 email@instarmac.co.uk www.instarmac.co.uk
<b>EMERGENCY TELEPHONE</b>	+44 (0)7971 217 347

**2 HAZARDS IDENTIFICATION**

Risk of serious damage to eyes. Irritating to respiratory system and skin.

**CLASSIFICATION** Xi;R37/38, R41.

**3 COMPOSITION/INFORMATION ON INGREDIENTS**

Name	EC No.	CAS-No.	Content	Classification
CRISTOBALITE FLOUR	238-455-4	14464-46-1	1-10%	Xn;R48/20.
SILICA SAND	238-878-4	14808-60-7	30-60%	-
VINYL ACETATE COPOLYMER			1-10%	-
WHITE OPC			10-30%	Xi;R41,R37/38.

The Full Text for all R-Phrases are Displayed in Section 16

**4 FIRST-AID MEASURES**

**GENERAL INFORMATION**

Risk of serious damage to eyes.

**INHALATION**

Move into fresh air and keep at rest. Get medical attention if any discomfort continues.

**INGESTION**

DO NOT INDUCE VOMITING! Immediately rinse mouth and drink plenty of water (200-300 ml).

**SKIN CONTACT**

Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if irritation persists after washing.

**EYE CONTACT**

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart. Continue to rinse for at least 15 minutes and get medical attention.

**5 FIRE-FIGHTING MEASURES**

**EXTINGUISHING MEDIA**

Water. Foam.

**SPECIAL FIRE FIGHTING PROCEDURES**

No specific fire fighting procedure given.

**UNUSUAL FIRE & EXPLOSION HAZARDS**

No unusual fire or explosion hazards noted.

**ULTRA FLEXJOINT WALL & FLOOR GROUT WHITE****6 ACCIDENTAL RELEASE MEASURES****PERSONAL PRECAUTIONS**

Wear protective clothing as described in Section 8 of this safety data sheet.

**ENVIRONMENTAL PRECAUTIONS**

Do not allow to enter drains, sewers or watercourses.

**SPILL CLEAN UP METHODS**

Remove spillage with vacuum cleaner. If not possible, collect spillage with shovel, broom or the like. Avoid generation and spreading of dust.

**7 HANDLING AND STORAGE****USAGE PRECAUTIONS**

Avoid spilling, skin and eye contact.

**STORAGE PRECAUTIONS**

Avoid frost. Store in closed original container at temperatures between 5°C and 30°C.

**8 EXPOSURE CONTROLS/PERSONAL PROTECTION**

Name	Std	TWA - 8 hrs		STEL - 15 min		Notes
CRISTOBALITE FLOUR	WEL		0.1 mg/m3 resp.dust			
SILICA SAND	WEL		0.3 mg/m3			
VINYL ACETATE COPOLYMER	WEL		4 mg/m3			
WHITE OPC	WEL		4 mg/m3			

WEL = Workplace Exposure Limit.

**PROTECTIVE EQUIPMENT****PROCESS CONDITIONS**

Provide eyewash station.

**ENGINEERING MEASURES**

Provide sufficient ventilation for operations causing dust formation.

**RESPIRATORY EQUIPMENT**

If ventilation is insufficient, suitable respiratory protection must be provided. Dust mask/respirator.

**HAND PROTECTION**

Use suitable protective gloves if risk of skin contact.

**EYE PROTECTION**

Wear dust resistant safety goggles where there is danger of eye contact.

**OTHER PROTECTION**

Wear appropriate clothing to prevent any possibility of skin contact.

**HYGIENE MEASURES**

Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes contaminated. When using do not eat, drink or smoke. Wash contaminated clothing before reuse.

**9 PHYSICAL AND CHEMICAL PROPERTIES**

APPEARANCE	Powder, dust
RELATIVE DENSITY	1.6-2.0 @ 20°C

**10 STABILITY AND REACTIVITY**

REVISION DATE: 13/11/2009

**ULTRA FLEXJOINT WALL & FLOOR GROUT WHITE****STABILITY**

Stable under normal temperature conditions and recommended use.

**MATERIALS TO AVOID**

Strong acids. Strong alkalis.

**11 TOXICOLOGICAL INFORMATION****INHALATION**

May cause damage to mucous membranes in nose, throat, lungs and bronchial system.

**INGESTION**

May cause discomfort if swallowed.

**SKIN CONTACT**

Prolonged contact with wet cement/mixture may cause burns.

**EYE CONTACT**

Risk of serious damage to eyes.

**12 ECOLOGICAL INFORMATION****ECOTOXICITY**

The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

**13 DISPOSAL CONSIDERATIONS****GENERAL INFORMATION**

Dispose of waste and residues in accordance with local authority requirements.

**14 TRANSPORT INFORMATION****GENERAL**

The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

**15 REGULATORY INFORMATION****LABELLING**

Irritant

**RISK PHRASES**

R37/38 Irritating to respiratory system and skin.

R41 Risk of serious damage to eyes.

**SAFETY PHRASES**

S24/25 Avoid contact with skin and eyes.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S37/39 Wear suitable gloves and eye/face protection.

S46 If swallowed, seek medical advice immediately and show this container or label.

S51 Use only in well-ventilated areas.

S64 If swallowed, rinse mouth with water (only if the person is conscious).

**UK REGULATORY REFERENCES**

Chemicals (Hazard Information &amp; Packaging) Regulations.

**ENVIRONMENTAL LISTING**

Control of Pollution Act 1974.

**EU DIRECTIVES**

Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC.

REVISION DATE: 13/11/2009

**ULTRA FLEXJOINT WALL & FLOOR GROUT WHITE****APPROVED CODE OF PRACTICE**

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply.

**GUIDANCE NOTES**

Workplace Exposure Limits EH40.

**NATIONAL REGULATIONS**

Workplace Exposure Limits 2005 (EH40) The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2007 (CDG 2007)

**16 OTHER INFORMATION****GENERAL INFORMATION**

If further information on training is required contact Instarmac Group plc

**REVISION DATE** 13/11/2009**REV. NO./REPL. SDS GENERATED** 3**RISK PHRASES IN FULL**

NC	Not classified.
R37/38	Irritating to respiratory system and skin.
R41	Risk of serious damage to eyes.
R48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation.

**DISCLAIMER**

The purpose of the above information is to describe the products only in terms of health and safety requirements. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. It is the users obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date specified.

All goods are supplied in accordance with Instarmac Group plc's general conditions of sale, copies of which may be obtained by telephoning sales on 01827 872244